

stick electrode inverter

- big range of supply voltage +/- 15%
- compact, portable
- stepless adjustable welding current
- functions electrode welding:
hot-start, arc-force, anti-stick
- TIG lift-arc welding
- thermal overload protection
- solid sheet steel case

- sign S

option:

- reduced open circuit voltage
- G 350 i: additional module for
cell-electrodes

G 250 i
G 350 i

MADE IN GERMANY



| technical data | | | G 250 i | G 350 i |
|----------------------------|-----------|-----------|-----------------|-----------------|
| supply voltage, 50 / 60 Hz | | | 400 V, 3 phase | 400 V, 3 phase |
| fuse | | | 16 A slow | 32 A slow |
| max. power draw | | | 12,3 kVA | 22 kVA |
| cos phi | | | 0,9 | 0,9 |
| setting range (stepless) | electrode | | 20 - 250 A | 20 - 350 A |
| | TIG | | 10 - 250 A | 10 - 350 A |
| operating voltage | electrode | | 20,4 - 30 V | 20,4 - 34 V |
| open circuit voltage | | | 85 V | 65 V |
| duty cycle 40°C | 35 % | electrode | 250 A / 30 V | ----- |
| | 80 % | electrode | ----- | 350 A / 34 V |
| | 100 % | electrode | 180 A / 27,2 V | 300 A / 32 V |
| system of protection | | | IP 23 | IP 23 |
| insulation class | | | F (155°C) | F (155°C) |
| system of cooling | | | F | F |
| weight | | | 18,5 kg | 19,5 kg |
| dimensions L x W x H (mm) | | | 500 x 250 x 430 | 500 x 250 x 430 |